



Specifications

Model Number: 10-1085
Input Voltage: 10-14 VDC
Lamp Types: See Chart
Size: 7.7" x 1.6" x 0.89"
Weight: 4.7 oz.
Mounting: Slotted Mounting Tabs
Note: Cap Off All Unused Tabs



10-1085 12V DC	 ATLANTIC ULTRAVIOLET CORPORATION® Hauppauge, NY 11788 631.273.0500 • www.ultraviolet.com www.buyultraviolet.com See instruction sheet for wiring information.	Supply Voltage: 12V DC Current (Max): 4.2 A Lamp Current: 0.39-0.45 A No. of Lamps: 1 Lamp Types: G36T5, GPH843T5, GPH1148T5 Ambient Temp: -5 to 104°F (-15°-40°C) Case Temp (Max): 158° F (70° C)	 Surelite™ ELECTRONIC BALLAST
---------------------------------	--	--	---

The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

Lamp Types

G36T5	Diagram #2
GPH843T5	Diagram #1
GPH1148T5	Diagram #1

This ballast may be acceptable for use with lamps not listed here. Contact us to discuss your requirement.

Connections

Diagram #1 - 2 Pins Each End - Rapid Start





Diagram #2 - 1 Pin Each End - Instant Start



The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.