

# GF72SSS/8 Grand™ Series Solid Door Freezers

Manufacturer:

SKU#: 8265-10-1102

- Available in 1, 2 and 3 doors
- Exterior cabinet front and sides are stainless steel; exterior top, back and bottom are galvanized steel
- Interior cabinet liner and door panel are stainless steel
- Adjustable temperature control range: -13°C to -30°C, factory preset at -20°C
- Top mounted key door locks
- Bottom mounted refrigeration system
- UL, C-UL, ETL Sanitation, ENERGY STAR® listed
- Warranties: 18 months parts and labor, 5 year compressor (US and Canada), 18 months parts (International)



## **Product Description**

Digital LED display microprocessor temperature controller Selectable °F or °C control Visual Hi/Lo temperature alarm Adjustable control range from -13°C to -30°C (-8.6°F to -22°F); factory preset at -20°C (-5°F) Door open alarm Continuous product temperature display Condenser cleaning reminder alarm Power supply switch Exterior cabinet front and sides are stainless steel Exterior cabinet top, back and bottom are galvanized steel Interior cabinet liner and interior door panel are stainless steel Cabinet and solid door are foamed-in- place with CFC-free high density polyurethane foam insulation Heavy duty solid door(s) with pivot hinges. Self- closing with 90° stay open feature Curved door handle(s) with recessed pocket(s) Magnetic door gaskets Top mounted key door lock(s) (2 keys) 4 casters (2 locking) on one and two door models, 6 casters (3 locking) on three door model (field installation required) 4 vinyl coated wire shelves per door section Perimeter anticondensate door frame heater wires Interior light, door switch activated Bottom mounted air cooled condensing unit Top mounted forced air cooling coil Automatic defrost and condensate evaporation Warranties: 18 month parts and labor, 5 year compressor (US and Canada), 18 months parts (International) UL, C-UL, ETL Sanitation, ENERGY STAR® listed

### GF72SSS/8 Grand™ Series Solid Door Freezers Specification

Grand™ Series Solid Door Freezers

SKU 8265-10-1026 Model No. GF23SSS/0

#### Specification

• Crated Weight (lbs)(kg): 308 (139)

Crated Height (in)(cm): 84-1/4
 (211)

Crated Width (in)(cm): 29-1/8 (73)

Crated Depth (in)(cm): 33-1/2 (84)Interior Height (in)(cm): 61 (153)

• Interior Width (in)(cm): 23-3/4 (59)

• Interior Depth (in)(cm): 27 (68)

1

8265-10-1027 GF49SSS/0

8265-10-1028 GF72SSS/8

- Overall Height (in)(cm): 83-3/4 (209)
- Overall Width (in)(cm): 27-1/2 (69)
- Overall Depth (in)(cm): 33 (83)
- Gross Cubage (CuFt)(L): 23.0 (651)
- Number of Shelves: 4
- Shelf Area (SqFt)(Sqm): 18.0 (1.67)
- Number of Casters: 4
- Condensing Unit Size: 1/2 HP
- Refrigerant: R-404a
- Total Amp Draw: 8.5
- Voltage Description: 115/60/1
- NEMA Plug Configuration: L14-20P
- Cord and Plug Furnished: Yes
- NEMA Receptacle: L14-20R
- Crated Weight (lbs)(kg): 483 (217)
- Crated Height (in)(cm): 84-1/4 (211)
- Crated Width (in)(cm): 56-3/4 (142)
- Crated Depth (in)(cm): 33-1/2 (84)
- Interior Height (in)(cm): 61 (153)
- Interior Width (in)(cm): 51-1/2 (129)
- Interior Depth (in)(cm): 27 (68)
- Overall Height (in)(cm): 83-3/4 (209)
- Overall Width (in)(cm): 55-1/4 (138)
- Overall Depth (in)(cm): 33 (83)
- Gross Cubage (CuFt)(L): 49.0 (1387)
- Number of Shelves: 8
- Shelf Area (SqFt)(Sqm): 39.0 (3.6)
- Number of Casters: 4
- Condensing Unit Size: 3/4 HP
- Refrigerant: R-404a
- Total Amp Draw: 9.5
- Voltage Description: 115/60/1
- NEMA Plug Configuration: 5-15P
- Cord and Plug Furnished: Yes
- NEMA Receptacle: 5-15R
- Crated Weight (lbs)(kg): 653 (294)
- Crated Height (in)(cm): 84-1/4 (211)
- Crated Width (in)(cm): 78-3/8 (196)
- Crated Depth (in)(cm): 33-1/2 (84)
- Interior Height (in)(cm): 61 (153)
- Interior Width (in)(cm): 74-1/4 (186)
- Interior Depth (in)(cm): 27 (68)
- Overall Height (in)(cm): 83-3/4
  (209)
- Overall Width (in)(cm): 78 (195)
- Overall Depth (in)(cm): 33 (83)
- Gross Cubage (CuFt)(L): 70.0

2

(2002)

• Number of Shelves: 12

• Shelf Area (SqFt)(Sqm): 56.5 (5.25)

• Number of Casters: 6

• Condensing Unit Size: 1/1 HP

• Refrigerant: R-404a • Total Amp Draw: 9.0 • Voltage Description: 115/208-230/60/1

• NEMA Plug Configuration: L14-20P • Cord and Plug Furnished: Yes

• NEMA Receptacle: L14-20R

#### WHY BUY FROM GMI?

Your trusted source for Used & New lab equipments, Parts, Factory Clearance instrument service since 1985.





instrument offerings.



We routinely save discerning laboratories Quality? ISO 9001:2008 certified means Warranties from 90 days to a year as well we remove 100% of the risk in buying 'used' laboratory equipment.



as multi-year service agreements are available.

GMI is an industry-leading distributor of brand new laboratory equipment and instruments. We supply a wide range of cutting-edge analytical instruments including centrifuges, gas chromatographs, freezers, thermal cyclers, and more. Choose from more than a thousand of new and innovative lab instruments that meet specifications and come with warranties up to 1 year.

