



NOTES:

1. INLET: 5/16" BARB
2. OUTLET: 5/16" BARB SHUTOFF W/ CHECK VALVE
3. GAUGE: 60#
4. SAFETY BLOW-OFF 60±5 PSI
5. WORKING PRESSURE: 0-50 PSI
6. POLY BONNET W/ GOLD ADJ CAP
7. MOUNTED ON S/S BRACKET

MATERIAL	NAME	DATE
	DRAWN	JPK 08/02/11
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:
REG, SEC, BEER, 60#, 5/16B IN, 5/16B-CV SHUTOFF, PLUG, POLY, GOLD, METAL BRCKT

SIZE	DWG. NO.	REV
A	T1661STC_SALES	C