

ANGULAR: MACH ± 1/2°

BEND ±

TWO PLACE DECIMAL ± 0.015

THREE PLACE DECIMAL ± 0.005

## **NOTES:**

- 1. INLET: 5/16" BARB
- 2. OUTLETS: 5/16" BARB W/ SHUT-OFFS
- 3. GAUGES: 60#
- 4. SAFETY BLOW-OFF: 60 ± 5 PSI. 5. WORKING PRESSURE: 0-50 PSI
- 6. BONNETS: POLY, GOLD

MATERIAL		NAME	DATE
	DRAWN	JPK	07/27/0
FINISH	ENG APPR.		
	PROPRIETARY		
DIMENSIONS ARE IN INCHES	AND CONFIDENTIAL		
	THE INFORMATION CONTAINED		
TOLERANCES:	IN THIS DRAWING IS THE SOLE		
FRACTIONAL ± 1/64	PROPERTY OF TAPRITE-FASSCO		

IN THIS DRAWING IS THE SOLE
PROPERTY OF TAPRITE-FASSCO
MFG., INC. ANY REPRODUCTION
IN PART OR AS A WHOLE WITHOUT
THE WRITTEN PERMISSION OF
TAPRITE-FASSCO MFG., INC.
IS PROHIBITED.



TITLE:

REG SEC BEER, 5P5P, 60#, 5/16B IN, 5/16B SHUTOFF, POLY GOLD

SIZE DWG. NO.

A T1695ST\_SALES

SCALE: 1:1 DO NOT SCALE
SHEET 1 OF 1