

Baker SterilGARD® III Advance SG403 & SG603 Safety Cabinets

Manufacturer: Baker

SKU#: 8038-30-1044

- · Vertical laminar flow
- Supply and exhaust HEPA filters
- Baker momentum air curtain
- High velocity air slots
- UniPressure Preflow plenum



Product Description

The Baker Company SterilGARD® III Advance is a Class II Type A/B3 biological safety cabinet designed with vertical laminar airflow and front access opening. Integrated with HEPA filters, the cabinet keeps the environment, the user and the product safe from airborne contaminants. The SterilGARD® III Advance is available in the 4-ft. SG403 and 6-ft. SG603 models. The SterilGARD® III Advance cabinet is equipped with The Baker Company's momentum air curtain, creating a faster airflow for an extremely effective air barrier. The biosafety cabinet is also equipped with high velocity air slots to maximize the cabinet's protective capability, and an airfoil design at the bottom of the sash to maximize containment without compromising comfort. Built for durability, the SterilGARD® III UniPressure Preflow plenums have been constructed entirely of metal for strength, air-tightness and resistance to deterioration. Additionally, the work surface is made of corrosion-resistant 16-gauge type 304 stainless steel, and are recessed to retain spills. The radiused cove corners make for easy cleaning. For convenience and easier operation, the scan-tested supply and exhaust HEPA filters are installed and removed through the front of the cabinet without entry into SterilGARD's work area. The SterilGARD® III Advance Biological Safety Cabinet is also manufactured with ergonomics in mind. The work area lighting system produces 100-foot candles of illumination at the surface, and access to it is made easy with the sliding view screen. The 10-degree sloped front feature also improves operator comfort and safety. Call us today to learn more about the SterilGARD® III Advance Biological Safety Cabinet!

Baker SterilGARD® III Advance SG403 & SG603 Safety Cabinets Specification

Baker SterilGARD® III Advance SG403 & SG603 Safety Cabinets Specifications

	Model SG403	Model SG603
Weight	525 lbs	700 lbs
Weight	625 lbs	810 lbs
with Optional Stand		
Electrical Specifications		115V AC, 1 Phase, 60 Hz
Blower Motor (1,625 RPM)	6.6 amps	9.9 amps
Fluorescent Light (ballast)	0.8 amps	0.8 amps
Duplex Outlets (G.F.I.)	5.0 amps	4.0 amps
Total Running Load	12.4 amps	14.7 amps
Environmental Conditions		Indoor use
		Altitudes up to 2000 meters
		Temperature range from 5° C to 40

1

WHY BUY FROM GMI?

Your trusted source for Used & New lab equipments, Parts, Factory Clearance instrument service since 1985.







Enjoy big savings on New Instrument Program.



Experience customer-driven services. We well as multi-year service agreements.

GMI is a ISO 9001:2008 certified company - your proof that your instrument purchase from GMI passes through rigorous refurbishing, recalibration, and recertification process, arriving at your laboratory in fully working order and defect free. We are not an auction company, nor are we an instrument broker... getting in the middle of 'deals'. All items come complete with the final QC date, engineer's ID# and a copy of test results / QC data, if applicable. Additionally, all items are thoroughly cleaned an professionally packaged / crated with care to ensure they arrive safely in your lab ready for professional installation.

