

Series 2612

Water Suction / Discharge Hose



This water suction hose is designed to handle a wide range of applications in industry, construction, and agriculture. The tough, flexible EPDM rubber construction will resist abrasion, weathering and the effects of agricultural herbicides and other mild chemicals. Incorporates a steel dual wire helix in the hose wall for full suction capabilities as well as high tensile tire cord fabric for discharge pressure.

Tube:	Black EPDM blend
Reinforcement:	Multiple textile plies with dual wire helix
Cover:	Black EPDM blend
Temperature:	-20°F to +200°F (-29°C to +93°C)
Branding:	Blue Mylar / White Letters

Part #	I.D. (In)	O.D. (In)	Bend Radius (In)	W.P. (PSIG)	Weight (Lbs / Ft)	Std. Length	Stock (Yes) or Min. Order
2612-100	1	1.30	4.0	150	.54	100'/200'	Yes
2612-125	1-1/4	1.65	5.0	150	.64	100'/200'	Yes
2612-150	1-1/2	1.89	6.0	150	.72	100'/200'	Yes
2612-200	2	2.44	7.0	150	1.08	100'/200'	Yes
2612-250	2-1/2	2.95	8.0	150	1.48	100'/200'	Yes
2612-300	3	3.46	10.0	150	1.80	100'/200'	Yes
2612-400	4	4.53	14.0	150	2.43	100'/200'	Yes
2612-600	6	6.61	30.0	150	4.16	100'	Yes
2612-800	8	8.70	38.0	150	9.32	20'	Yes
2612-1000	10	10.87	50.0	150	12.40	20'	Yes
2612-1200	12	12.87	66.0	150	16.70	20'	Yes