

Series 2618

Fire Engine Pump Hose



Series 2618 is a premium quality, heavy-duty fire engine suction/discharge hose. This hose is designed for severe applications requiring endurance and higher pressure ratings. The unique design allows for extreme flexibility, and high kink resistance when making tight bends. The tough, flexible EPDM synthetic rubber provides resistance to abrasion, weathering, and heat.

Tube:	Black EPDM blend
Reinforcement:	Multiple textile plies with dual wire helix
Cover:	Black EPDM blend
Temperature:	-30°F to +200°F (-34°C to +93°C)
Design Factor:	4 : 1
Branding:	Embossed

Part #	I.D. (In)	O.D. (In)	Bend Radius (In)	W.P. (PSIG)	Weight (Lbs / Ft)	Std. Length	Stock (Yes) or Min. Order
2618-100	1	1.56	4.0	300	.70	100'	400'
2618-150	1-1/2	2.06	5.0	300	1.07	100'	400'
2618-200	2	2.56	6.0	300	1.51	100'	400'
2618-250	2-1/2	3.15	7.0	300	2.11	100'	400'
2618-300	3	3.70	8.0	300	2.41	100'	400'
2618-400	4	4.75	10.0	300	3.71	100'	400'
2618-500	5	5.75	14.0	300	5.10	100'	400'

- Note: O.D. tolerance $\pm 1/32"$ (.032).
- Note: Above hose can be rated for 400 PSI working pressure utilizing a 3:1 safety factor. The burst pressure will remain at 1200 PSI.