

Series 3010 Hydraulic Jack Hose



Hydraulic hose used for high-pressure jack line applications. Meets Material Handling Institute Specification 1J-100 (July 1979) for hydraulic hose and assemblies and in jacking systems. **Factory Assembly Only.**

| | |
|-----------------------|---|
| Tube: | Class A maximum oil resistant synthetic rubber. |
| Reinforcement: | Two braids of high tensile steel wire. |
| Cover: | Black oil and abrasion resistant. MSHA fabric impression cover. |
| Temperature: | -40° F. to +212° F. (-40° C. to +100° C.) |
| Branding: | Embossed. |

| Part # | Inside Diameter | | Outside Diameter | | W.P. (PSI) | Min. Burst PSI | Minimum Bend Rad (In.) | Weight Lbs/Ft | Couplings |
|---------|-----------------|-----|------------------|------|---------------|-------------------|------------------------------|------------------|-----------|
| | In. | MM | (In.) | (MM) | | | | | |
| 3010-04 | 1/4 | 6.4 | 0.59 | 15.0 | 10,000* | 20,000 | 2.2 | 0.19 | KW |
| 3010-06 | 3/8 | 9.5 | 0.75 | 19.1 | 10,000* | 20,000 | 3.7 | 0.29 | KW |

* Static, non-impulse pressure rating for hydraulic jack applications.