

ASSEMBLY MATERIALS:

THREADED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES


90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	425-050-4	+/- 4"	28.25"	11.75"	1075	
	.75"	425-075-4	+/- 4"	29.5"	12.875"	792	
	1.00"	425-100-4	+/- 4"	33.875"	14"	571	
	1.25"	425-125-4	+/- 4"	36.25"	15.25"	531	
	1.50"	425-150-4	+/- 4"	38.625"	16.25"	472	
	2.00"	425-200-4	+/- 4"	43.375"	18.25"	516	
	2.50"	425-250-4	+/- 4"	51.625"	21.5"	387	
	3.00"	425-300-4	+/- 4"	56"	22.875"	316	
	4.00"	425-400-4	+/- 4"	65.375"	26"	232	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP THREADED ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 425-4.idw		SCALE: NONE	