



**ASSEMBLY MATERIALS:**

**THREADED FITTINGS:** CARBON STEEL SCH 40

**HOSE/BRAID:** STAINLESS STEEL 300 SERIES

**90° ELBOWS:** CARBON STEEL SCH 40 LR

**45° ELBOWS:** CARBON STEEL SCH 40



FOR FIRE PROTECTION SYSTEMS

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	426-050-4	+/- 4"	28.25"	11.75"	300	
	.75"	426-075-4	+/- 4"	29.5"	12.875"	300	
	1.00"	426-100-4	+/- 4"	33.875"	14"	300	
	1.25"	426-125-4	+/- 4"	36.25"	15.25"	300	
	1.50"	426-150-4	+/- 4"	38.625"	16.25"	300	
	2.00"	426-200-4	+/- 4"	43.375"	18.25"	300	
	2.50"	426-250-4	+/- 4"	51.625"	21.5"	300	
	3.00"	426-300-4	+/- 4"	56"	22.875"	300	
	4.00"	426-400-4	+/- 4"	65.375"	26"	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
<b>UNISOURCE MFG.</b>			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
<b>UNISOURCE FIRE V</b> THREADED ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 426-4.idw		SCALE: NONE	