



FOR FIRE PROTECTION SYSTEMS

ASSEMBLY MATERIALS:

GROOVED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	436-150-4	+/- 4"	40.625"	16.25"	300	
	2.00"	436-200-4	+/- 4"	45.375	18.25"	300	
	2.50"	436-250-4	+/- 4"	52.625"	21.5"	300	
	3.00"	436-300-4	+/- 4"	56"	22.875"	300	
	4.00"	436-400-4	+/- 4"	63.375"	26"	175	
	5.00"	436-500-4	+/- 4"	72.5"	29.875"	175	
	6.00"	436-600-4	+/- 4"	79"	32.25"	175	
	8.00"	436-800-4	+/- 4"	93"	36.875"	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE FIRE V GROOVED ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 436-4.idw		SCALE: NONE	