

**ASSEMBLY MATERIALS:**

**HOSE/BRAID:** STAINLESS STEEL 300 SERIES


**90° ELBOWS:** CARBON STEEL SCH 40 LR

**45° ELBOWS:** CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	430-050-2	+/- 2"	18.875"	8.5"	1075	
	.75"	430-075-2	+/- 2"	19.375"	9.375"	792	
	1.00"	430-100-2	+/- 2"	22.75"	10.5"	571	
	1.25"	430-125-2	+/- 2"	25.25"	11.625"	531	
	1.50"	430-150-2	+/- 2"	26.875"	12.25"	472	
	2.00"	430-200-2	+/- 2"	30.875"	14"	516	
	2.50"	430-250-2	+/- 2"	36.75"	16.5"	387	
	3.00"	430-300-2	+/- 2"	39.375"	17.5"	316	
	4.00"	430-400-2	+/- 2"	46"	20.25"	232	
	5.00"	430-500-2	+/- 2"	53.875"	23.5"	191	
	6.00"	430-600-2	+/- 2"	59.25"	25.5"	165	
	8.00"	430-800-2	+/- 2"	70.875"	29.75"	234	
	10.00"	430-1000-2	+/- 2"	83.5"	34.75"	230	
	12.00"	430-1200-2	+/- 2"	94.25"	38.5"	161	
	14.00"	430-1400-2	+/- 2"	106"	42.75"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO [WWW.UNISOURCE-MFG.COM](http://WWW.UNISOURCE-MFG.COM) FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
<b>UNISOURCE V-LOOP</b> WELD ENDS - +/- 2" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 430-2.idw		SCALE: NONE	