

ASSEMBLY MATERIALS:

HOSE/BRAID: STAINLESS STEEL 300 SERIES


90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	430-050-4	+/- 4"	25.25"	11.75"	1075	
	.75"	430-075-4	+/- 4"	26.5"	12.875"	792	
	1.00"	430-100-4	+/- 4"	29.875"	14"	571	
	1.25"	430-125-4	+/- 4"	32.25"	15.25"	231	
	1.50"	430-150-4	+/- 4"	34.625"	16.25"	472	
	2.00"	430-200-4	+/- 4"	39.375"	18.25"	516	
	2.50"	430-250-4	+/- 4"	46.625"	21.5"	387	
	3.00"	430-300-4	+/- 4"	50"	22.875"	316	
	4.00"	430-400-4	+/- 4"	57.375"	26"	232	
	5.00"	430-500-4	+/- 4"	66.5"	29.875"	191	
	6.00"	430-600-4	+/- 4"	73"	32.25"	165	
	8.00"	430-800-4	+/- 4"	85"	36.875"	234	
	10.00"	430-1000-4	+/- 4"	99"	42.875"	230	
	12.00"	430-1200-4	+/- 4"	111"	47.375"	161	
	14.00"	430-1400-4	+/- 4"	124"	51.875"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP WELD ENDS - +/- 4" MOVEMENT			
DRAWN BY:	BC	DATE:	06/15/15
DWG NO:	430-4.idw	SCALE:	NONE