

ASSEMBLY MATERIALS:

GROOVED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES


90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	435-150-2	+/- 2"	32.875"	12.25"	472	
	2.00"	435-200-2	+/- 2"	36.875"	14"	516	
	2.50"	435-250-2	+/- 2"	42.75"	16.5"	387	
	3.00"	435-300-2	+/- 2"	45.375"	17.5"	316	
	4.00"	435-400-2	+/- 2"	52"	20.25"	232	
	5.00"	435-500-2	+/- 2"	59.875"	23.5"	191	
	6.00"	435-600-2	+/- 2"	65.25"	25.5"	165	
	8.00"	435-800-2	+/- 2"	78.875"	29.75"	234	
	10.00"	435-1000-2	+/- 2"	91.5"	34.75"	230	
	12.00"	435-1200-2	+/- 2"	102.25"	38.5"	161	
	14.00"	435-1400-2	+/- 2"	114"	42.75"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP GROOVED ENDS - +/- 2" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 435-2.idw		SCALE: NONE	