

FOR FIRE PROTECTION SYSTEMS


ASSEMBLY MATERIALS:

- GROOVED FITTINGS:** CARBON STEEL SCH 40
- HOSE/BRAID:** STAINLESS STEEL 300 SERIES
- 90° ELBOWS:** CARBON STEEL SCH 40 LR

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	436U-150-8	+/- 8"	21"	25"	300	
	2.00"	436U-200-8	+/- 8"	22.875"	28.75"	300	
	2.50"	436U-250-8	+/- 8"	25"	34"	300	
	3.00"	436U-300-8	+/- 8"	27"	36.75"	300	
	4.00"	436U-400-8	+/- 8"	31"	42.75"	175	
	5.00"	436U-500-8	+/- 8"	36"	49.75"	175	
	6.00"	436U-600-8	+/- 8"	42"	54.875"	175	
	8.00"	436U-800-8	+/- 8"	56"	64.375"	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GOT TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE FIRE U GROOVED ENDS - +/- 8 MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 436-8.idw		SCALE: NONE	