



SVx - - - - - TP HF - - - - -

Code name (to be specified by AmbaFlex) :

SVX - belt width - central diam. - pitch - material - windings - configuration - speed - transport dir. - TP belt type HF high friction

<b>Dimensions</b>		(H1)	Bottom roller height :	----- mm
		(H3)	Top roller height :	----- mm
		(H2)	Height difference :	----- mm
		(B)	Belt width :	<input type="checkbox"/> SVx-2/200-1200-DL (2 x 200 mm) <input type="checkbox"/> SVx-2/300-1600-DL (2 x 300 mm) <input type="checkbox"/> SVx-2/400-1700-DL (2 x 400 mm)
		<b>Configurations:</b> <input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/> E <input type="checkbox"/> F <input type="checkbox"/> G <input type="checkbox"/> H <input type="checkbox"/> L <input type="checkbox"/> R <input type="checkbox"/> A <input type="checkbox"/> A		

<b>Application</b>	<b>Transport direction :</b> <input type="checkbox"/> up (TU) <input type="checkbox"/> down (TD) <input type="checkbox"/> reversible (TA) <input type="checkbox"/> up / down (TU/TD) <input type="checkbox"/> down / up (TD/TU)
	<input type="checkbox"/> <b>single drive system :</b> <input type="checkbox"/> speed belt ----- m/min
	<input type="checkbox"/> <b>dual drive system :</b> <input type="checkbox"/> synchronised angular speed: in feed speed ___ m/min <input type="checkbox"/> dual speed inner belt speed ___ m/min outer belt speed ___ m/min
	<i>example of synchronised angular speed</i>
	<b>Additional options :</b> <input type="checkbox"/> centre guide <input type="checkbox"/> machine suited for container transport <input type="checkbox"/> integrated frequency controller on drive(s)
<b>Use :</b> <input type="checkbox"/> lift <input type="checkbox"/> buffer ----- m/length <input type="checkbox"/> buffer ----- items <input type="checkbox"/> combination	
<b>Start / stop operation :</b> <input type="checkbox"/> no (only emergency stop) <input type="checkbox"/> yes : no. of stop per hour ----- <input type="checkbox"/> product indexing	
<b>Environment :</b> <input type="checkbox"/> dry environment (S) <input type="checkbox"/> wet environment (CR) <input type="checkbox"/> wet environment (RS)	

<b>Products to be transported</b>	<b>Type :</b>
	<input type="checkbox"/> Different : -----
<b>Contact materials :</b> <input type="checkbox"/> Carton <input type="checkbox"/> Soft paper <input type="checkbox"/> Metal <input type="checkbox"/> Hard plastic <input type="checkbox"/> Soft plastic <input type="checkbox"/> Glass <input type="checkbox"/> Wood	
<b>Special :</b> <input type="checkbox"/> Shrink wrapped in foil <input type="checkbox"/> Cross strapped <input type="checkbox"/> Ribbed bottom <input type="checkbox"/> Different : -----	

		Dimensions (LxWxH) (mm)	Leading side	Weight (kg)	Throughput (items/min)	Average load (kg/m)
<b>Inner belt</b>	Minimum	----- x ----- x -----	<input type="checkbox"/> short side <input type="checkbox"/> long side	-----	-----	-----
	Maximum	----- x ----- x -----	<input type="checkbox"/> short side <input type="checkbox"/> long side	-----	-----	-----
<b>Outer belt</b>	Minimum	----- x ----- x -----	<input type="checkbox"/> short side <input type="checkbox"/> long side	-----	-----	-----
	Maximum	----- x ----- x -----	<input type="checkbox"/> short side <input type="checkbox"/> long side	-----	-----	-----