

# Air King™ Accessories

## Features:

- The use of an Air King™ safety clip or wire type retainer is necessary to ensure couplings will not become accidentally disconnected. This guarantees the fittings are properly connected as the pin will not go through the holes in the mating flanges until couplings are locked in place.
- only one Air King™ safety clip or wire type retainer is required for each Air King™ universal coupling

## Standard Safety Clip



### Feature:

- same size clip can be used for all coupling sizes

Wire Diameter	Part #	Price/E	Pkg Qty
.080	<b>AC1</b>	<b>\$0.30</b>	25 / bag only

## Air King Safety Pins



### Feature:

- heavy duty, oversized

Wire Diameter	Part #	Price/E
.058	<b>AKSP1</b>	<b>\$1.30</b>
.091	<b>AKSP25</b>	<b>1.45</b>

## Stainless Steel Clip



### Feature:

- same size clip can be used for all coupling sizes

Wire Diameter	Part #	Price/E
.072	<b>AC7</b>	<b>\$2.25</b>

## Lanyards



### Features:

- synthetic cord
- same size for all coupling sizes

Part #	Price/E	Pkg Qty
<b>ACL8</b>	<b>\$0.40</b>	25 / bag only



### Features:

- breaking strength: 160 lbs.
- overall length: 7" eye to eye

304 stainless Part #	Price/E
<b>LR7</b>	<b>\$8.00</b>

## Washers




AWR4



AWS6



AWR14



### Features:

- 2 lug couplings use the same size washer (AWR4, AWS6)
- 4 lug couplings use the same size washer (AWR14)
- rubber temperature range: **-20°F to 160°F**
- neoprene temperature range: **-20°F to 190°F**
- neoprene is oil resistant

Part #	Material	Style	Price/E	Pkg Qty
<b>AWR4<sup>1</sup></b>	<i>rubber</i>	2 lug	<b>\$0.60</b>	50 / bag only
<b>AWS6</b>	<i>neoprene</i>	2 lug	<b>0.80</b>	50 / bag only
<b>AWR14</b>	<i>rubber</i>	4 lug	<b>4.40</b>	---

<sup>1</sup> made from Styrene-butadiene (SBR)