Brass Push-In Fittings

Features:

- saves up to 75% of assembly time compared to the standard compression fittings
- quick connect: simply push tubing in, no tools required
- quick disconnect: hold two fingers on insert and pull tubing out, no tools required
- reusable: connect and disconnect numerous times
- full flow design provides up to 60% more flow than conventional fittings with internal tube supports
- positive seal: no leaks, after tubing is inserted, seal is made
- secure tube retention: pulling on tubing only serves to tighten the connection
- pre-applied PTFE based pipe sealant on all male pipe threads saves customer additional labor
- working pressure: fittings are suitable for use up to the maximum working pressure of the plastic tubing used also suitable for vacuum service
- temperature range: -10°F to 200°F

F

Male Connectors



tube to male NPTF

Tube	Male	Brass		Opt
OD	NPTF	Part #	Price/E	Qty
1/8"	10-32 ¹	684X10	\$10.70	20
1/8"	1/8"	684X4	7.70	20
5/32"	10-32 ¹	685X10	9.20	20
5/32"	1/8"	685X4	6.50	20
5/32"	1/4"	685X8	8.80	10
3/16"	10-32 ¹	686X10	10.40	20
3/16"	1/8"	686X4	8.75	20
1/4"	10-32 ¹	688X10	9.60	20
1/4"	1/8"	688X4	5.35	20
1/4"	1/4"	688X8	5.80	10
1/4"	3/8"	688X12	10.20	10
3/8"	1/8"	6812X4	7.70	10
3/8"	1/4"	6812X8	7.55	10
3/8"	3/8"	6812X12	8.70	10
3/8"	1/2"	6812X16	13.85	5
1/2"	1/4"	6816X8	12.40	5
1/2"	3/8"	6816X12	12.65	5
1/2"	1/2"	6816X16	16.10	5

Female Connectors



tube to female NPTF

Tube	Female	Brass		Opt
OD	NPTF	Part #	Price/E	Qty
1/8"	1/8"	664X4	\$17.40	10
5/32"	1/8"	665X4	14.35	10
1/4"	1/8"	668X4	10.00	10
1/4"	1/4"	668X8	13.00	10
3/8"	1/4"	6612X8	14.05	10
3/8"	3/8"	6612X12	19.00	5

Unions



tube to tube

Tube OD	Brass		Opt
Tube OD	Part #	Price/E	Qty
1/8"	624	\$9.00	20
5/32"	625	9.85	10
1/4"	628	9.00	10
3/8"	6212	11.00	10
1/2"	6216	14.30	5

Bulkhead Unions



tube to male thread

Tube Thread		Brass		Opt
OD	Tilload	Part #	Price/E	Qty
1/8"	7/16"-20	824	\$24.50	10
5/32"	7/16"-20	825	23.00	10
1/4"	1/2"-20	828	16.50	10
3/8"	3/4"-16	8212	23.00	5
1/2"	15/16"-16	8216	34.00	5

DPL116

¹ UNF - Straight thread, supplied with gasket