# KPC 82011



#### **Description**

Chesterton® KPC 820N is the premium product of choice when searching for an environmentally compliant solution to your plant's degreasing needs. It is an oil and grease cutting liquid, completely miscible in water.

Containing no chlorinated solvents, caustics, butyl compounds, phosphate or petroleum distillates, Chesterton KPC 820N is the safe alternative for all degreasing applications.

Chesterton KPC 820N will provide efficiency not usually seen in other "safe" cleaners. It quickly removes metal working fluids of all kinds, grease, grime and other soils common to industrial production areas. When used at elevated temperatures, the cleaning action is accelerated. The heaviest grime can be removed easily at temperatures of 60°C (140°F) to 82°C (180°F).

Chesterton KPC 820N is cost efficient. To meet individual cleaning requirements and determine needed solution strengths, field evaluation is necessary. The heaviest industrial grime may require a more concentrated solution, while light soils can be removed with as little as a 1-2% concentration.

### **Composition**

Chesterton KPC 820N contains only one category of raw materials; those that provide the difficult balance of environmental acceptability, worker safety and performance.

Instead of harsh alkalies, toxic solvents and phosphates, Chesterton KPC 820N is formulated with several unique ingredients which synergistically act to provide degreasing power without harmful side effects.

Chesterton KPC 820N is much more than a simple "green" cleaner – it is a powerful performer that works in heavy industry as well as light commercial and institutional facilities.

Typical physical properties	
Form	Liquid
Color	Green
Appearance	Clear, transparent
Odor	Mild/Swee
Solubility in water	Infinite
Density wt/gal	8.6 lbs
Specific Gravity	1,03
Boiling point	100°C (212°F
Flash point	None
Fire point	None
Freezing point	0°C (32°F
pH (Concentrate)	9.8
Freeze thaw stability	Passes 6 cycles

#### Quickly and efficiently removes

- Oily deposits
- Soot and exhaust residue
- Metal working fluids
- Animal and vegetable fats
- Lubrication compounds
- Other soils common to industrial production areas

#### **Features**

- Nonflammable
- Nontoxic
- Biodegradable
- Phosphate free
- Highly dilutable
- Safe on most metals
- USDA authorized
- No offensive odor
- Moderate pH

# Recommended starting dilutions - Check label

	Dilution
General cleaning	up to 20 -1
Light oils	up to 30 -1
Soot, diesel fuels etc.	up to 20 -1
Machining fluids	up to 30 -1
Waxy films	up to 2 -1
Heavy grime	up to 5 -1

Water

## Safety

Before using this product, review the Material Safety Data Sheet (MSDS) or the appropriate safety sheet for your area.



DISTRIBUTED BY:

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. CHESTERTON CO. DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.

FORM NO. E70132 REV. 4/95