

THE WORLD LEADER IN CLEAN AIR SOLUTIONS

DriPak® 2000

SYNTHETIC EXTENDED SURFACE POCKET FILTERS

Engineering Data Supplement to Bulletin AFP-1-114

Nominal Size (inches) (W x H x D)	Pockets Per Filter	Rated Airflow Capacity (CFM) By *Rated Filter Face Velocity			Gross Media Area (sq. ft.)	*Rated Initial Resistance (in. w.g.) Average Efficiency			
		375 FPM	500 FPM	625 FPM		MERV 15	MERV 14	MERV 12	
		Recommended final resistance is 1.0 in. w.g. for all models.							
24 x 24 x 36	9			2500	117	.49	.44	.40	--
24 x 24 x 36	8		2000		104	.34	.33	.24	--
24 x 24 x 36	7		2000		91	.37	.36	.27	--
24 x 24 x 36	6		2000		78	.38	.37	.30	--
24 x 20 x 36	6		1675		69	.38	.37	.30	--
20 x 24 x 36	6			2075	78	.40	.39	.32	--
20 x 24 x 36	5		1675		65	.38	.37	.30	--
20 x 20 x 36	5		1400		58	.37	.36	.27	--
12 x 24 x 36	4		1000	1250	52	.34	.33	.24	--
12 x 24 x 36	3		1000		39	.38	.37	.30	--
24 x 24 x 30	10		2000		107	.42	.39	.34	--
24 x 24 x 30	8		2000		85	.36	.35	.26	--
24 x 24 x 30	6		2000		64	.45	.40	.30	--
24 x 20 x 30	6		1675		54	.45	.40	.30	--
20 x 24 x 30	6		1675		64	.40	.39	.32	--
20 x 24 x 30	5		1675		53	.45	.40	.30	--
20 x 20 x 30	6		1400		57	.38	.37	.30	--
12 x 24 x 30	5		1000		53	.34	.33	.24	--
12 x 24 x 30	4		1000		43	.37	.36	.27	--
12 x 24 x 30	3		1000		32	.45	.40	.30	--
24 x 24 x 26	8		2000		74	.41	.39	.32	--
24 x 24 x 26	6		2000		55	.48	.44	.34	--
12 x 24 x 26	4		1000		37	.41	.39	.32	--
12 x 24 x 26	3		1000		28	.48	.44	.34	--
24 x 24 x 21	10		2000		75	.45	.40	.30	--
24 x 24 x 21	8		2000		60	.45	.40	.30	--
24 x 24 x 21	6	1500			45	.45	.40	.30	--
24 x 20 x 21	8		1675		53	.45	.40	.30	--
24 x 20 x 21	6	1250			40	.45	.40	.30	--
20 x 24 x 21	6		1675		45	.50	.45	.35	--
20 x 24 x 21	5	1250			37	.45	.40	.30	--
20 x 20 x 21	6		1400		40	.48	.44	.34	--
20 x 20 x 21	5	1050			33	.45	.40	.30	--
12 x 24 x 21	5		1000		37	.41	.39	.32	--
12 x 24 x 21	4		1000		30	.45	.40	.30	--
12 x 24 x 21	3	750			22	.45	.40	.30	--
24 x 24 x 19	6		2500		41				.32
24 x 20 x 19	6		2075		37	--	--	--	.32
20 x 24 x 19	5		2075		34	--	--	--	.32
20 x 20 x 19	5		1750		30	--	--	--	.32
12 x 24 x 19	3		1250		21	--	--	--	.32
24 x 24 x 15	10	1500			53	.44	.39	.29	--
24 x 24 x 15	8		2000		43	--	--	--	.25
24 x 24 x 15	6	1500			32	.62	.52	.40	--
24 x 20 x 15	6		1675		29	--	--	--	.32
20 x 24 x 15	5		1675		27	--	--	--	.32
20 x 20 x 15	5		1400		24	--	--	--	.32
12 x 24 x 15	5	750			27	.44	.39	.29	--
12 x 24 x 15	3	750			16	.62	.52	.40	--
12 x 24 x 15	3		1000		16	--	--	--	.29
24 x 24 x 12	6		2000		26	--	--	--	.32
24 x 20 x 12	6		1675		23	--	--	--	.29
20 x 25 x 12	6		1750		27	--	--	--	.29
20 x 24 x 12	5		1675		22	--	--	--	.32
20 x 20 x 12	5		1400		19	--	--	--	.32
16 x 25 x 12	5		1400		22	--	--	--	.29
16 x 20 x 12	4		1100		15	--	--	--	.32
12 x 24 x 12	3		1000		13	--	--	--	.32

*All performance data is based on ASHRAE Standard 52.2. Performance tolerances conform to Section 7.4 of ARI Standard 850-93.




BETTER AIR IS OUR BUSINESS®

DriPak® 2000


Performance Data

Initial Resistance vs. Filter Face Velocity



MERV 15, MERV 14 & MERV 12 based on 24" x 24" x 30" - 8 pocket filter.
MERV 8 based on 24" x 24" x 19" - 6 pocket filter.

Composite Minimum Efficiency Curve



Tested in accordance with ASHRAE Standard 52.2.

Product Information

Efficiencies

MERV 15, MERV 14, and MERV 12

Face Dimensions: 24 x 24, 24 x 20, 20 X 24, 20 x 20, and 12 x 24

Depths: 12, 15, 21, 26, 30 and 36

MERV 8

Face Dimensions: 24 x 24, 24 x 20, 20 X 25, 20 x 24, 20 x 20, 16 X 25, 16 x 20, and 12 x 24

Depths: 12, 15, 19, 22, and 30

DriPak 2000 filters are available in pocket and face dimension combinations from 12 x 24 - 3-pocket to 24 x 24 - 10-pocket.

Gaskets and Loops

Gaskets, for side access systems or other applications which require gaskets, and pocket support loops are available on all DriPak 2000 filters.

Classification

DriPak 2000 filters are UL Classified. Testing was performed according to UL Standard 900 and ULC-S111.

Temperature Limits

DriPak 2000 filters, operating with fan on, are designed for a continuous operating temperature of 200° F or 93° C.

DriPak® is a registered trademark of AAF International in the U.S. and other countries.



AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

ISO Certified Firm

©2015 AAF International

AFP-7-114C 02/15