

Haynes Manufacturing Company

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Haynes Manufacturing Co. Emergency Phone (440) 871-2188 24142 Detroit Rd. Contact: Beth Kloos

Westlake, Ohio 44145, USA

PRODUCT NAME: :HAYNES HOMOGENIZER OIL

PRODUCT DESCRIPTION:
INTENDED USE
CHEMICAL FAMILY:
FORMULA:
PRODUCT CODE:
:Base Oil and Additives
:Circulating/gear oil
:NOT APPLICABLE
:NOT APPLICABLE

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

No Reportable Hazardous Substance(s) or Complex Substance(s).

SECTION 3 – HAZARD IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

POTENTIAL HEALTH EFFECTS:

Low order of toxicity. Excessive exposure may result in eye, skin, and respiratory irritation. High-pressure injection under skin may cause serious damage.

NFPA Hazard ID: Health: 0 Flammability: 1 Reactivity: 0 **HMIS Hazard ID:** Health: 0 Flammability: 1 Reactivity: 0

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks, which may vary from person to person.

Revision Date: 10/10/13 Page 1 of 8



Haynes Manufacturing Company

SECTION 4 – FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

<u>SECTION 5 – FIRE FIGHTING MEASURES</u>

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (C02) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaced and to protect personnel.

Unusual Fire Hazards: Pressurized mists may form a flammable mixture.

Hazardous Combustion Products: Alehydes, Oxides of carbon, Incomplete combustion products, Sulfur oxides, Smoke, Fume

FLAMMABILITY PROPERTIES

Flash Point [Method]: >234C (453F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Revision Date: 10/10/13 Page 2 of 8



Haynes Manufacturing Company

Autoignition Temperature: N/D

<u>SECTION 6 – ACCIDENTAL RELEASE MEASURES</u>

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment, which exceed the applicable reportable quantity or oil spills, which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.

SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIROMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

<u>SECTION 7 – HANDLING AND STORAGE</u>

HANDLING

Prevent small spills and leakage to avoid slip hazard.

STATIC ACCUMLATOR: This material is a static accumulator.

STORAGE: Do not store in open or unlabelled containers.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur, the following are recommended: 5 mg/m³-ACGIH TLV, 10 mg/m³-ACGIH STEL, 5 mg/m³-OSHA PEL.

Revision Date: 10/10/13 Page 3 of 8



Haynes Manufacturing Company

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider: No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

RESPIRATORY PROTECTION

If engineering controls do not maintain airborne contaminant concentrations at a level, which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

HAND PROTECTION

Any specific glove information provided is based on published literature and glove manufacturer data. Work conditions can greatly affect glove durability; inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

EYE PROTECTION

If contact is likely, safety glasses with side shields are recommended.

SKIN AND BODY PROTECTION

Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

SPECIFIC HYGIENE MEASURES

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIROMENTAL CONTROLS

See Sections 6, 7, 12, 13

Revision Date: 10/10/13 Page 4 of 8



Haynes Manufacturing Company

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

GENERAL INFORMATION

Physical State: Liquid
Color: Brown
Odor: Characteristic

Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIROMENTAL INFORMATION

Relative Density (at 15C): 0.89

Flash Point [Method]: >234C (453F) [ASTM D-92]

Flammable Limits (Approximate Volume % in air): LEL: 0.9 UEL: 7.0

Autoignition Temperature: N/D

Boiling Point/Range: >316C (600F) **Vapor Density (Air=1):** >2 at 101 kPa

Vapor Pressure: <0.013 kPa (0.1 mm Hg) at 20C

Evaporation Rate (n-butyl acetate=1): N/D pH: N/A
Log Pow (n-Octanal/Water Partition Coefficient: >3.5
Solubility in Water: Negligible

Viscosity: 220 cSt (220 mm2/sec) at 40C

Oxidizing Properties: See Sections 3, 15, 16

OTHER INFORMATION

Freezing Point: N/D Melting Point: N/A

Pour Point: -12°C (10°F) **DMSO Extract (mineral oil only), IP-346:** <3%wt

SECTION 10 -STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

Revision Date: 10/10/13 Page 5 of 8



Haynes Manufacturing Company

<u>SECTION 11-TOXICOLOGICAL INFORMATION</u>

ACUTE TOXICITY

| Route of Exposure | Conclusion/Remarks |
|--------------------------------------|--|
| Inhalation | |
| Toxicity (Rat): LC50>5000 mg/m3 | Minimally Toxic. Based on assessment of the components. |
| Irritation: No end point data. | Negligible hazard at ambient/normal handling temperature. Based on assessment of the components. |
| Ingestion | |
| Toxicity (Rat): LD50>2000 mg/kg | Minimally Toxic. Based on test data for structurally similar materials. |
| Skin | |
| Toxicity (Rabbit): LD50>200mg/kg | Minimally Toxic. Based on test data for structurally similar materials. |
| Irritation (Rabbit): Data available. | Negligible irritation to skin at ambient temperatures. Based on assessment of the components. |
| Eye | |
| Irritation (Rabbit): Data available. | May cause mild, short-lasting discomfort to eyes. Bases on assessment of the components. |

CHRONIC/OTHER EFFECTS

Contains:

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

Additional information is available by request.

The following ingredients are cited on the lists below: None.

REGULATORY LIST SEARCHED

1=NTP CARC 3=IARC 1 5=IARC 2B 2=NTP SUS 4=IARC 2A 6=OSHA CARC

SECTION 12 – ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

Revision Date: 10/10/13 Page 6 of 8



Haynes Manufacturing Company

EXOTOXICITY

Material—Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component—Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component—Expected to be inherently biodegradable.

BIOACCUMLATION POTENTIAL

Base oil component—Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

<u>SECTION 13 – DISPOSAL CONSIDERATIONS</u>

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Products is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrositivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedures (TCLP). However, used product may be regulated.

Empty Container Warning

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

<u>SECTION 14 – TRANSPORT INFORMATION</u>

LAND (DOT): Not regulated for Land Transport

LAND (TDG): Not regulated for Land Transport

SEA (IMDG): Not regulated for Sea Transport according to IMDG-Code

Revision Date: 10/10/13 Page 7 of 8



Haynes Manufacturing Company

AIR (IATA): Not regulated for Air Transport

<u> SECTION 15 – REGULATORY INFORMATION</u>

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

NATIONAL CHEMICAL INVENTORY LISTING: TSCA, AICS, PICCS, ENCS, DSL, EINECS, IECSC, KECI

EPCRA: This material contains no extremely hazardous substances.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None

SARA (313) TOXIC RELEASE INVENTORY: The material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The Following Ingredients are Cited on the Lists Below: None.

| 1=ACGIH ALL | 6=TSCA 5a2 | 11=CA P65 REPRO | 16=MN RTK |
|-------------|----------------|-----------------|-----------|
| 2=ACGIH A1 | 7=TSCA 5e | 12=CA RTK | 17=NJ RTK |
| 3=ACGIH A2 | 8=TSCA 6 | 13=IL RTK | 18=PA RTK |
| 4=OSHA Z | 9=TSCA 12b | 14=LA RTK | 19=RI RTK |
| 5=TSCA 4 | 10=CA P65 CARC | 15=MI 293 | |

Code key: CARC-Carcinogen; REPRO=Reproductive

<u>SECTION 16 – OTHER INFORMATION</u>

N/D=Not Determined, N/A=Not Applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

No revision information is available

WE BELIEVE THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE, BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE, OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.

Revision Date: 10/10/13 Page 8 of 8