

# MASTER SKIN PACKAGER by Ampak

MODEL: MP



## FEATURES

### CONTROL PANEL

- PLC with Color HMI Controls
- Adjustable Pre-Heat, Heat And Cool Package Time Functions

### HEATING OVEN

- Stationary Oven With Safety Guard
- Patented Spirad Instant-On Heating Elements
- Adjustable Oven Height

### SEALING PLATFORM

- Variable Speed Turbine Vacuum System
- Pneumatic Film Frame Drive
- Hot Wire Cutoff

### OTHER FEATURES

- Spindle Film Roll Holder
- Multiple Platen Sizes: 24" - 36" Wide, 30" - 72" Long
- One Year Warranty



Model MP2436A

## MODEL SPECS

<b>PLATEN SIZE</b>	From 24" by 30" to 36" by 72" (From 64 cm by 76 cm to 91 cm by 183 cm)
<b>PLATEN CLEARANCE</b>	Factory Adjustable 9"-20" (23-51 cm); Standard Setting 19" (48 cm)
<b>PLATEN HEIGHT</b>	40" (102 cm)
<b>FILM CAPACITY</b>	From 26" to 38" Depending on Model (66 cm to 97 cm)
<b>OVERALL DIMENSIONS</b>	Depends on Model
<b>POWER REQUIREMENTS</b>	220 Volt (Amps depend on Size) Three Phase
<b>AIR REQUIREMENTS</b>	1 CFM @ 80 PSI
<b>VACUUM</b>	(A) 1, 2, or 3 Hivac Turbine Vacuum Motors 96 cfm, 6.5" Hg. each; (B) Turbine plus 1/4 HP Pos. Disp. Pump, 21 Gal. Tank, 25" Hg.
<b>WEIGHT</b>	(A) 500 lbs. (190 kg); (B) 575 lbs. (227 kg)

## AVAILABLE OPTIONS

- Models Available

Platen Size	Model A— Turbine Vacuum	Model B— Positive Displacement
24" W, 24" L	MP2424A	MP2424B
24" W, 30" L	MP2430A	MP2430B
24" W, 36" L	MP2436A	MP2436B
30" W, 36" L	MP3036A	MP3036B
30" W, 48" L	MP3048A	MP3048B
36" W, 36" L	MP3636A	MP3636B
36" W, 48" L	MP3648A	MP3648B
36" W, 54" L	MP3654A	MP3654B
36" W, 60" L	MP3660A	MP3660B
36" W, 72" L	MP3672A	MP3672B

- Energy Miser Film Temperature Sensing System
- Extended Cooling Cycle for Energy Miser Probe
- Special Electrical For 440-480 Volts
- Special Size Film Frame Insert And Platen
- Automatic Blowoff System For Vacuum Forming - Positive Displacement System Only
- Automatic Film Frame (Standard on MP-3048 and larger)
- Automatic Platen Lift
- Automatic Infeed And Outfeed Electrical Interface



Revised 2013