

# SHIPMATE SKIN PACKAGING SYSTEM by Ampak

MODEL: SP1824A, EZ-24, OF-24



Shipmate SP1824A with EZ-24 and OF-24 shown

This skin packaging system is made up of three components: an automatic infeed, the Shipmate skin packaging machine, and an automatic outfeed. For larger formats, the Master skin packaging machine is also available.

## FEATURES

### EZ INFEED

- Power and Controls from host skin machine
- Soft-Start Eliminates Product Movement
- Optional Stationary Template for Loading Accuracy and Speed

### SHIPMATE SKIN PACKAGER

- PLC controls with Touch Screen Access
- Energy Saving Instant-On Spirad™ Oven
- Variable Speed Turbine Vacuum System

### EZ OUTFEED

- Protective Covers for Operator Safety
- Virtually Maintenance Free Design

### ROTOCUT DIE CUTTER

- Bi-Flex Cutting Principle (Cutting Force Concentrated Between 2 Pressure Rolls)
- Powered 6" Diameter Rigid Steel Pressure Rollers
- Heavy Duty Self Aligning Roller Bearings



Rotocut RC2400

## SYSTEM SPECS

|  |   |
|--|---|
| <b>PLATEN SIZE</b>                     | 18" W, 24" L (46 W, 61 L cm)  |
| <b>MAX PRODUCT HEIGHT &amp; WEIGHT</b> | 5" (12 cm)<br>20 lbs. (9 kg)  |
| <b>PLATEN HEIGHT</b>                   | 40" (102 cm)  |
| <b>FILM CAPACITY</b>                   | 20" W, 9" OD, 3" ID<br>(51 W, 23 OD, 7.5 ID cm)   |
| <b>OVERALL DIMENSIONS</b>              | SP1824A: 43" W, 39" D, 60" H<br>(109 W, 99 D, 152 H cm)<br>EZ-24: 24 1/2", 56" (62 cm, 140 cm)<br>OF-24: 34", 96 1/4" (85 cm, 241 cm) |
| <b>POWER REQUIREMENTS</b>              | 208 Volt, 41 Amps, Single Phase   |
| <b>AIR</b>                             | 2 cfm @ 80psi   |

## ROTOCUT SPECS

|                           |   |
|---------------------------|---|
| <b>CUTTING AREA</b>       | 18" W, 24" L (46 W, 61 L cm)                    |
| <b>OVERALL DIMENSIONS</b> | 43" W, 90" L, 53" H<br>(109 W, 229 L, 135 H cm) |
| <b>POWER REQUIREMENTS</b> | 115, 208, 230 Volt, Single Phase,<br>15 Amp     |

